



### Purchase

Purchase



### Overview

Model Name	APC Power-Saving Timer Essential SurgeArrest, 4 Outlet Wall Tap, 120V
Includes	User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla,Aruba,Bahamas,Barbados,Belize,Bermuda,Brazil,Canada,Colombia,Costa Rica,Cuba,Dominican Republic,Ecuador,El Salvador,Finland,Guatemala,Guyana,Haiti,Honduras,Jamaica,Mexico,Nicaragua,Paraguay,Puerto Rico,Trinidad And Tobago,Turks And Caicos Islands,United States,Venezuela,VIRGIN ISLANDS (UNITED STATES)

### Output

Number of Outlets	4
Receptacle Style	NEMA 5-15R

### Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz
Input Connections	NEMA 5-15P
Maximum Input Current	15

### Surge Protection and Filtering

Surge energy rating	1080
EMI/RFI Noise rejection (100 kHz to 10 mHz)	40
Peak Current Common Mode	72
NM Surge Response Time (ns)	1
Let Through Voltage Rating	< 400

### Physical

Net Weight	0.25 kg
Maximum Height	165 mm
Maximum Width	94 mm
Maximum Depth	51 mm
Shipping Weight	0.56 kg

Shipping Height	245 mm
Shipping Width	226 mm
Shipping Depth	67 mm
Master Carton Units	6.0
Master Carton Dimensions (Length x Width x Height)	504 mm x 308 mm x 297 mm
Master Carton Weight	3.58 kg
SCC Codes	1073130426926 4
Color	White
Units per Pallet	288.0

### Environmental

Operating Environment	0 - 45 °C
Operating Relative Humidity	0 - 95
Operating Elevation	0-3000 meters
Storage Temperature	-5 - 45 °C
Storage Relative Humidity	0 - 95
Storage Elevation	0-15000 meters

### Conformance

Regulatory Approvals	ETL,UL 1449
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : \$50000
UL 1449 TVSS Rating	<400V

### Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs